

US006546830B2

(12) United States Patent

Kanazawa

(56)

(10) Patent No.:

US 6,546,830 B2

(45) Date of Patent:

Apr. 15, 2003

(54)	TRANSMISSION DEVICE OF FOUR-WHEEL DRIVE VEHICLE							
(75)	Inventor:	Kazuo Kanazawa, Tokyo (JP)						
(73)	Assignee:	Fuji Jukogyo Kabushiki Kaisha, Tokyo (JP)						
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.						
(21)	Appl. No.: 09/951,765							
(22)	Filed:	Sep. 13, 2001						
(65)	Prior Publication Data							
US 2002/0066324 A1 Jun. 6, 2002								
(30)	Foreign Application Priority Data							
Sep.	14, 2000	(JP) 2000-280602						
(51)	Int. Cl.7.	F16H 37/06 ; F16H 3/08						
(58)	Field of Search 74/665 R, 665 F,							
		74/665 G, 665 GC, 329, 330, 331, 333;						

References Cited

U.S. PATENT DOCUMENTS

5,123,293 A	٠	6/1992	Umemoto et al 74/333
5,640,882 A	*	6/1997	Meuller 74/333 X
5,947,218 A	*	9/1999	Ishimaru 74/665 G X
6,044,720 A	•	4/2000	Matsufuji 74/331
6,332,371 B1	•	12/2001	Ohashi et al 74/331

FOREIGN PATENT DOCUMENTS

JР	7-167257		7/1995	
JP^	362178429 A	٠	8/1997	180/233


^{*} cited by examiner

Primary Examiner-Richard M. Lorence Assistant Examiner—Roger Pang
(74) Attorney, Agent, or Firm—McGinn & Gibb, PLLC

ABSTRACT

A transfer drive gear is provided at the rear end of a hollow counter shaft disposed under an input shaft. A reduction driven gear is provided at the rear end of a front drive shaft inserted in the counter shaft. The transfer drive gear and the reduction driven gear are engaged with a transfer driven gear which is integrally formed with an intermediate output shaft and a reduction drive gear. The rear end side of the intermediate output shaft is coupled with the front end side of a rear drive shaft through a torque coupling device, so that an FF based on the four-wheel drive vehicle can be formed.

13 Claims, 5 Drawing Sheets



180/233